



# EXPLOSION PROOF GAS SENSOR/TRANSMITTER

Gas Detection For Life

“S” Series



## Features

- Explosion proof housing
- Patented water repellent sensor coating
- Operates independent of a controller
- Available for LEL, H<sub>2</sub>S, CO, O<sub>2</sub>, and ppm HC
- IR sensors available for LEL & CO<sub>2</sub>
- Long life sensors (2 + years typical)
- Competitively priced
- Intrinsically safe, U.L. Classified CSA

## Applications

- Petrochemical Plants
- Refineries
- Gas Plants
- Offshore Drilling Platforms
- Water & wastewater treatment plants
- Pulp & paper mills
- Gas, telephone, & electric utilities
- Parking garages
- Manufacturing facilities
- Steel
- Automotive
- Chemical storage buildings

The RKI “S” series gas sensor/transmitters are highly reliable and cost effective basic 4-20 mA transmitters for detection of common gas hazards. The “S” series transmitters are available for LEL, O<sub>2</sub>, H<sub>2</sub>S, CO, CO<sub>2</sub> or for 0 - 2,000 ppm Hydrocarbon detection (for various fuels or solvents). The electronics are encased inside a potted package to avoid damage from mechanical abuse or corrosion, and the amplifier is installed inside an explosion-proof enclosure. All sensors are explosion-proof with flame arrestors and approved for use in hazardous atmospheres. There is also an optional version for oxygen for use in non-hazardous atmospheres.

The only tools required to calibrate the “S” series are a voltmeter, screwdriver, and cal gas. The zero and calibration functions are performed by adjusting potentiometers on the amplifiers. The amplifier has test jacks for connecting to a voltmeter for calibration purposes, and the sensor response is viewed on the voltmeter as a 100mV to 500mV signal. Field calibration can be performed easily and quickly by one person.

The “S” series transmitters can be used either indoors or outdoors. The flame arrestors utilize a patented coating which make them water repellent, and splash guards are also available for use in very wet environments.

The transmitter operates from 24 VDC (10.5VDC to 30 VDC), and provides a 4-20mA signal which can be connected to a wide variety of controllers.

# "S" Series

	LEL	O2	H2S	CO	Infrared			HC
					CO2	CH4	HC	
<b>Part #</b>	65-2400RK 65-2400RK-05	65-2513RK 65-2516RK	65-2422RK-05	65-2432RK-05	65-2391RK-03	65-2390RK-CH4	65-2390RK-HC	65-2460RK 65-2460RK-05
<b>Measuring Range</b>	0-100% LEL	0-25% Vol.	0-100 ppm	0-300 ppm	0-5% Vol.	0-100% LEL		0-2,000 ppm
<b>Max Current Draw</b>	200 mA (power wires) 25 mA (signal wires) 3 or 4 wires	25 mA (2 wire system)			60 mA (power wires) 25 mA (signal wires) 3 wires			100 mA (power wires) 25 mA (signal wires) 3 wires
<b>Outputs</b>	4 - 20 mA signal							
<b>Response Time</b>	30 seconds to 90% of concentration	20 seconds to 90% of concentration	45 seconds to 90% of concentration	30 seconds to 90% of concentration				
<b>Operating Environment</b>								
<b>Location</b>	Indoor or outdoor. Explosion proof for Class I, Div. 1, Groups B, C, and D.	Indoor or outdoor. Explosion proof housing (65-2516RK) and intrinsically safe sensor (65-2513RK)	Indoor or outdoor. Explosion proof for Class I, Div. 1, Groups B, C, and D.					
<b>Temperature</b>	-40 to 185° F	-4 to 113° F			-4 to 122° F		30 to 120° F	
<b>Humidity</b>	0 - 99% RH, non condensing							5 - 95% RH, non condensing
<b>Housing</b>	Aluminum explosion proof enclosure							
<b>Sensors</b>								
<b>Type</b>	Catalytic Combustion	Galvanic Cell	Electrochemical		Infrared			Metal Oxide Semiconductor
<b>Life Expectancy</b>	1 to 2 years with normal intermittent exposure to flammable gas	2 years normal service	2 years normal service when intermittently exposed to H2S	2 to 3 years normal service	5 + years normal service			5 to 10 years typical
<b>Controls</b>								
<b>Zero</b>	Sets transmitter output to 4 mA with 0% LEL output from combustible sensor	Sets transmitter output to 4 mA with an inert gas (zero) output from O2 sensor	Sets transmitter output to 4 mA with zero output from H2S sensor	Sets transmitter output to 4 mA with zero output from CO sensor	Sets transmitter output to 4 mA with zero output from CO2 sensor	Sets transmitter output to 4 mA with 0% LEL output from combustible sensor		Sets transmitter output to 4 mA with zero ppm output from sensor
<b>Span</b>	Sets transmitter output to 20 mA with 100% LEL output from combustible sensor	Sets transmitter output to 17.44 mA with 20.9% Vol. O2 (fresh air) output from O2 sensor	Sets transmitter output to 20 mA with 100 ppm output from H2S sensor	Sets transmitter output to 20 mA with 300 ppm output from CO sensor	Sets transmitter output to 20 mA with 5% volume output from CO2 sensor	Sets transmitter output to 20 mA with 100% LEL output from combustible sensor		Sets transmitter output to 20 mA with 2,000 ppm Hexane (typical) output from sensor
<b>Operating Voltage</b>	11 VDC to 30 VDC							
<b>Approvals</b>	65-2400RK UL 65-2400RK-05 CSA	65-2516RK CSA	CSA	CSA	UL			65-2460RK UL 65-2460RK-05 CSA
<b>Warranty</b>	One year materials and workmanship							

Specifications subject to change without notice.

Made in the USA



A9812



ISO 9001:2000



Certified AIR SAFETY  
2233 NW 23<sup>rd</sup> Ave.  
Portland, OR 97210  
Tel: 503-226-2109  
Fax: 503-226-0988

[info@certifiedAIRSAFETY.COM](mailto:info@certifiedAIRSAFETY.COM)  
[www.certifiedAIRSAFETY.COM](http://www.certifiedAIRSAFETY.COM)